



KOAMTAC

HF Reader KDC470/475Companion

Barcode and HF Reader in One

Enhance your KDC470/475 barcode scanner with HF reading. The reader connects directly to the KDC to give your smart device an all-in-one data collection solution whether you're using barcodes or HF tags—or a combination of the two.

Modular and Ergonomic Design

The KDC470/475 with HF Companion attaches to any smart device via a custom case for a sled solution. This unique modular design protects your investment as your business evolves.

Comparable HF readers are bulky and unwieldy; KOAMTAC's HF readers are lightweight and fit for the shape of your hand.

Diverse Bluetooth® Profiles

HID, SPP, and MFi allow seamless connectivity to any mobile device. Direct physical connection available for select devices.

Built for the Toughest Conditions

The KDC470/475 and HF Reader are IP65-rated meaning they're dust tight and water resistant. Plus, they can handle a 5' drop.

Rechargeable Batteries

Both 1-Slot and 4-Slot Charging Cradles are available for charging the HF Reader, KDC470/475, and host device. Get a full day of power from one charge or easily swap out batteries to keep going from shift to shift.

Onboard Storage

8MB of onboard memory allows you to record and store data and run basic applications directly on the KDC470/475.

Ideal for:

- ▶ Asset Management
- ▶ Inventory Management
- ▶ Utilities/Field Services
- ▶ Healthcare
- ▶ Aerospace

HF Companion Details

RFID Details

Standards Supported: ISO/IEC 14443 A/B, ISO/IEC 15693, FeliCa, MIFARE (1K/4K/Ultralight/Ultralight C/DESFire)
Nominal Read Range: Up to 3.42" (87 mm)
dependent on tag type
Frequency: 13.56 MHz

Functionality

Memory Flash ROM: 256 KB Program, 8MB User Data (KDC470/475)
Memory RAM: 64KB (KDC470/475)
Stores: 409,600 RFID tags (ISO/IEC 15693 UID Data)

User Environment

Operating: -4°F to 122°F (-20°C to 50°C)
Storage: -4°F to 140°F (-20°C to 60°C)
Humidity: 5% to 95% (non-condensing)

Physical Dimensions

(without KDC)
2.36" x 4.11" x 0.39"
(60 mm x 104.5 mm x 10 mm)

Weight

(without KDC)
1.35 oz (38.5 g)

Compliance

R&TTE, FCC, KC, TELEC, VCCI, SRRC, and RoHS Compliant



116 Village Blvd, Suite 305, Princeton, NJ 08540 USA
T: +1-609-256-4700 F: +1-609-228-4373
info@koamtac.com www.koamtac.com

© 2019 KOAMTAC, Inc.
KDC470RFID — 190910