

KOAMTAC KDC[®]200 1D Laser Bluetooth

A New Wave in Auto-ID

The KDC200 enables diverse mobile Auto-Identification applications for collecting and storing barcode data.

A built-in display eliminates blind erroneous data collection and enables interactive processes.

Included is an easy-to-replace rechargeable battery that can charge from any USB port. With 8MB of on-board memory that stores over 400,000 UPC product barcodes, memory shortages are no longer a concern.

ADVANCED FEATURES

- Ultra-Compact & Lightweight
- Class2 Bluetooth[®] with HID/SPP/MFi Profiles
- Supports USB HID/Flash Memory
- Bright 1" OLED display
- Rechargeable Li-Poly Battery
- Stores 400,000+ UPC Product Barcodes
- KTSvnc for:
 - Keyboard Wedging
 - Application Generation
 - DB Lookup
 - Inventory Management

Barcode Scanner & Data Collector

All KDC® products come with KTSync® software with keyboard wedging, application generation, database look up, inventory management, and KDC configuration features for Android, iOS, and Windows devices. Complementary SDK and technical support from top engineers and the development team ensure ease of data collection in any situation.



© 2021 KOAMTAC, Inc. KDC200 - 210121



KOVMLVC

1D Laser Bluetooth Barcode Scanner & Data Collector

Hardware Specifications

Physical Characteristics Size: 1.37" x 2.44" x 0.59" (35 mm x 62 mm x 15 mm) Weight : 1.2 oz (34g)

Electrical Characteristics Battery: Lithium-Polymer (3.7V DC, 200mAh) Charging: USB connector

Interfaces

Bluetooth V2.1+EDR, Class 2, HID/SPP/MFi USB to Serial (Ultra mini USB port) USB HID/Flash Memory

User Environment

Regulatory Conformance

Scan Range (10mil Code39)

Symbologies

Drop Spec: 4' (1.22 m) with protective boot Operating: 32°F to 113°F (0°C to 45°C) Storage: -4°F to 113°F (-20°C to 45°C) Humidity: 5% to 85% (non-condensing)

Laser Safety: IEC60825/CDRH Class II

Laser: 1.97" to 7.48" (50 mm to 190 mm)

R&TTE, FCC, KC, TELEC, VCCI, SRRC, RoHS Compliant

Laser (1D): EAN-13, EAN-8, UPC-A, UPC-E, Code 39, ITF14,

Code 35, Bookland EAN-13, EAN-13/8 incl. add on, UPC-A/E incl. add on, GS1 Omni, GS1 Limited, GS1 Expanded

Code 128, Interleaved 2 of 5, Codabar, GS1-128, Code 93,

Performance

Functionality

Memory Flash ROM: 256KB Program, 8MB User Data Memory RAM: 64KB

Wedging & Synchronization

Store to a file or transfer to an application Keyboard wedge function Add-on prefixes and suffixes Barcode option selection

Application Generation

SDK for PC and smartphone application Application generation tool Database lookup and Inventory Management features

OS Support

Android, iOS, Mac OS X, Windows

Your KDC

Models KDC200M, KDC200iM

Compatible Accessories

Charging Cradle KDC200 Ring Scanner KBD401K Dongle

Package Contents

1 x KDC200 Barcode Scanner 1 x KDC Lanyard 1 x Protective Boot 1 x KDC Ultra Mini USB Cable







© 2021 KOAMTAC, Inc. KDC200 - 210121





