
#### What's in the Box?

- 1 x KDC470/KDC475 Pistol Grip Adapter
- 1 x Pistol Grip
- 1 x Li-ion Battery (6000mAh) (optional)
- 4 x screws + 1 extra



\*KDC470/475 sold separately.
Tweezers and PH0 screwdriver (not included)
will be necessary to complete assembly.

### Additional KDC470/475 Accessories:


- 1-Slot Charging Cradle
- Extended Battery

# ΚΟΛΜΤΛΟ

116 Village Blvd, Ste 305, Princeton, NJ 08540 +1 609-256-4700 p | +1 609-228-4373 f info@koamtac.com | www.koamtac.com



KDC470/475 Pistol Grip Assembly Manual




### **Assembly Instructions:**

1. Using tweezers, carefully remove all four (4) screw caps from back of KDC470/475. (A)



2. Remove all four (4) screws from back of KDC470/475. (B)




3. Remove cover plate from back of KDC470/475. (C)



 Align screw holes of Pistol Grip Adapter with screw holes of KDC470/475. Use four (4) included screws to attach Pistol Grip Adapter to KDC470/475.



5. Align notch in top of Pistol Grip with top notch of the Pistol Grip Adapter. (E)




6. Slide Pistol Grip up until it clicks. (F)



#### **Removing Pistol Grip**

Squeeze tabs on both sides of the Pistol Grip Adapter and slide the Pistol Grip down. Pull the Pistol Grip away from the Pistol Grip Adapter and KDC470/475.



3. Close the battery door and turn the battery door knob clockwise to lock. (J)



#### 6000mAh Li-ion Battery Installation (Optional)

1. Turn knob on the bottom of the Pistol Grip counter-clockwise to open the battery door. (H)



## **Pistol Grip Battery Status**



When the device is charging

Red: Low Battery Orange: Charging Green: Fully Charged

When the battery is in use and device is discharging

Blinking Red: Low Battery Blinking Orange: Discharging Blinking Green: Fully Charged

\*The LED (Light Emitting Diode) blinks when the battery is being used .

2. Insert the battery into the Pistol Grip. (I)



## **KDC475 with Pistol Grip**



\*Assembly procedure is the same as KDC470.